Technical Data




Rated Voltage:	DC 1000V
•••••••••••••	••••••••••••••••••••••••••••••••••••
••••••••••••••••••••••••k•••	20
••••••••••••••••••	•••
•••••••••••••••••••• •:	•••• ••••
Altitude(m):	⩽2000
Weight(g):	10

Material Details

Part Name	Cap	Body	Fuse Element	Arc-extinguishing Agent
Material	Copper	Aluminium Oxide	Silver	Silica

BX0234



* For more information, please contact LEADER GROUP sales team: info@leadergroup-cn.com

DC FUSE HOLDER

Technical Data



PV0191-1P




PV0191-1P-A


Pole:	1P
Fuse Link Size(mm):	10x38
Rated Voltage(V):	DC1000
Rated Current(A):	32
DIN Rail(mm):	35
Weight(g):	60～61

Material Details

Part Name	Plastic Cement	Copper
Material	PBT(V-0)	Copper

Dimension Drawing





* For more information, please contact LEADER GROUP sales team: info@leadergroup-cn.com

DC FUSE HOLDER



PV0191-2P PV0191-3P PV0191-4P


Technical Data

Pole:	2P 3P 4P
Fuse Link Size(mm):	10x38
Rated Voltage(V)	DC1000
Rated Current(A):	32
DIN Rail(mm):	35
Weight(g):	2P:120 3P:182 4P:243

Material Details

Part Name	Plastic Cement	Copper
Material	PBT(V-0)	Copper

Dimension Drawing



* For more information, please contact LEADER GROUP sales team: info@leadergroup-cn.com

Power Loss

Model	Rated Current (Amps)	Joule Integral $I^2t(A^2s)$		Power Loss(W)	
		Pre-Arcing	Total at 1000V	0.8In	1.0In
PV0191	1	0.15	0.4	0.8	1.5
	2	1.2	3.4	0.6	1.0
	3	4	11	0.8	1.3
	4	9.5	26	1.0	1.5
	5	19	50	1.0	1.6
	6	30	90	1.1	1.8
	8	3	32	1.2	2.1
	10	7	70	1.2	2.3
	12	12	120	1.5	2.7
	15	22	220	1.7	2.9
	20	34	350	2.1	3.6

Characteristics Curve

Environmental Temperature and Fuse Reduction Coefficient Characteristics

